60W Single Output Class Ⅱ DIN Rail Power



CASE:918B 78x 93x 56 mm

- Universal AC input / Full range
- Installed on DIN rail TS35 / 7.5 or 15
- Protections: Short circuit / Overload / Over voltage
- Isolation Class Ⅱ
- Approvals: UL / CUL / TUV / CB / CE
- LED indicator for power on
- Cooling by free air convection
- 100% full load burn-in test
- 3 years warranty

AC input voltage range	88~264VAC; 124~370VDC
AC inrush current	Cold start, 27A at 115VAC, 36A at 230VAC
DC adjustment range	±10% rated output voltage
Overload protection	105%~160% constant current limiting, auto-recovery
Over voltage protection	115%~135% rated output voltage
Setup, rise, hold up time	100ms, 30ms, 60ms at full load and 230VAC
Withstand voltage	I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1minute
Working temperature	-20~45°C@100%, 60°C@60% load
Safety standards	UL60950-1, TUV EN60950-1 approved
EMC standards	EN55022 class B, EN61000-3-2,3, EN61000-6-2, EN61000-4-2,3,4,5,6,8,11, ENV50204, EN61204-3
Connection	I/P: 2 poles, O/P: 4 poles screw DIN terminal
Packing	0.3kg ; 48pcs / 15.4kg / 1.02CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
11251	DR-60-5	5V, 0~6.5A	±2%	80mV	76.0%
11252	DR-60-12	12V, 0~4.5A	±1%	120mV	82.0%
11253	DR-60-15	15V, 0~4.0A	±1%	120mV	83.0%
11254	DR-60-24	24V, 0~2.5A	±1%	150mV	84.0%